



## ADMIXTURE GUIDE

### POZZOLANIC MIXWATER TREATMENT (“PMT” Admixtures)

#### Liquid & Powder Admixtures

	PMT 1 CONCRETE			PMT 2 STUCCO	POLYMER LIQUID	POLYMER POWDER
	PMT-1-RM	PMT-1-OS	PMT-1-PC	PMT-2-SM	PMT-1-LS	Repair+
APPLICATION	READY MIX	READY MIX	PRECAST	STUCCO	CONCRETE	REPAIR MIXES
SELF CURE	YES	YES	YES	YES	NA	STANDARD
SLAB CURL	REDUCED	REDUCED	REDUCED	NA	NA	NA
SHRINKAGE	REDUCED	REDUCED	REDUCED	REDUCED	REDUCED	REDUCED
CRACKING	REDUCED	CONTROLLED	CONTROLLED	REDUCED	USE EPC	USE EPC
MOLD/MILDEW	REDUCED	ELIMINATED	REDUCED	REDUCED	USE EPC	USE EPC
EFFLORESC.	REDUCED	REDUCED	REDUCED	CONTROLLED	REDUCED	USE EPC
WATERPROOF	YES	YES	YES	YES	NA	USE EPC
VAPOR TRANS.	USE EPC	USE EPC	USE EPC	NA	NA	NA
CORR. INHIBIT	YES	YES	YES	NA	NA	NA
RESIST CHEM.	YES	YES	YES	YES	NA	NA
BLEEDWATER	REDUCED	REDUCED	REDUCED	REDUCED	REDUCED	REDUCED
HYDRATION	IMPROVED	IMPROVED	IMPROVED	IMPROVED	STANDARD	STANDARD
PASTE QUAL.	EXCELLENT	EXCELLENT	EXCELLENT	VERY GOOD	IMPROVED	IMPROVED
SEGREGATION	NONE	NONE	NONE	NA	NA	NA
WORKABILITY	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT	IMPROVED	STANDARD
SET TIME	STANDARD	STANDARD	STANDARD	ACCELERATED	STANDARD	VARIABLE

MIX INFO						
MAX. W/C ratio	.65	.65	.65	.6	.55	NA
METERING	5 to 8.5 ml/Kg.	5 to 8.5 ml/Kg.	5 to 8.5 ml/Kg.	5 to 8.5 ml/Kg.	2 to 6 ml/Kg.	5 to 8.5 ml/Kg.
BATCHING	PLANT	PLANT	PLANT	MIXER	VARIABLE	ON SITE

WARRANTY	1 Yr. Ltd. Extended available	1 Yr. Ltd. Extended available	1 Yr. Ltd. Extended available	1 Yr. Ltd. Extended available	1 Yr. Ltd. extended available	1 Yr. Ltd. Extended available
INSTALLATION*	PRODUCER	CONTRACTOR	PRODUCER	CONTRACTOR	PRODUCER	CONTRACTOR

#### EXAMPLE APPLICATIONS

FOOD PROCESSING	HEALTH CARE FACILITIES	POTABLE WATER RES.	SEWAGE TREATMENT	SECONDARY CONTAINMENT	MARINE CONCRETES	CAST-IN-PLACE WALKS
PRECAST CONCRETE	ARCHITECT. CONCRETES	BRIDGES AND PRESTRESSED	RESIDENTIAL FOUNDATIONS	SHOTCRETE APPLICATIONS	MORTARS AND STUCCO	DUSTPROOF APPLICATIONS

**All products cure clear for architectural surfaces.**

\* Company service consultants can be contracted for warranty approved installation of Enhance materials.  
SEE MANUFACTURER FOR SPECIFIC APPLICATIONS

**Note:**

**No admixture of any type or amount should be considered a substitute for good concreting practice.**

Revised 01/01/01